



IT 90 Stud Welding Unit

for ARC stud welding according to current standards

Technical Data

Gas/Automation/Process control Series/Series

Welding range M3 to M24, dia. 2 to 22 mm

Welding material Mild steel, stainless steel, aluminum

Welding rate Dia. 22 = 6 studs/min

Welding current 2,000 A (max.)

Current adjustment range 300 to 2,000 A (stepless)
Welding time 5 to 1,500 msec (stepless)

Primary power 400 V, 3 phases, 50/60 Hz, 63 AT (alternative input voltages available)

Primary plug 63 A (with 400 V mains)

Connected load 100 KVA (with 400 V mains)

Cooling type F (temperature controlled cooling fan)

Protection class IP 23

Operational and storage conditions
According to current standards

Dimension L x W x H 650 x 560 x 1,290 mm (without handle)

Weight 140 kg

Order No. 93-60-12096 (Gas/Automation/Process control/1 Gun connection)

93-60-42096 (Gas/Automation/Process control/4 Gun connections)

General Information

Application

· Especially suitable for thicker sheets of about 2 mm or higher

Process variants

- · Short cycle drawn arc welding
- Drawn arc welding

Equipment

- Welding with ceramic ferrule (series)
- Welding with shielding gas (series)
- Automation (series)
- Process sequence control (series)



Advantages

Features

- Microcontroller for precise process times, optimal functional reliability and maximum operating convenience
- Function monitoring automatic function test following power-up; monitoring of all internal system functions
- Lift test for gap welding guns and stud welding heads
- Library function automatic specification of welding current and welding time through selection of stud diameter according to welding range (with and without shielded gas); fine adjustment via arrow keys
- Process monitoring recording and analysis of factors affecting the welding process; after each weld, the reference
 and actual values are compared; display of the welding energy input; switchable automatic welding stop if limits are
 exceeded
- RS232 interface for data output; data and time of day are stored; welding parameters of each weld are logged)
- 4 gun connections (optional)

Structure

- Extremely easy to operate
- Compact
- **Mobile** highly mobile thanks to compact dimensions and low weight (50% weight savings vis-à-vis conventional stud welding units)
- Robust metal housing withstands rough treatment in shop and on site

Safety

- With integrated mains filter (protection against voltage peaks)
- Optimal for construction sites with large mains voltage fluctuations use even with critical voltage supply (- 10% + 10%)
- EMC test
- High-voltage test with log
- Retriggering lock-out prevents welding on a welding element that has already been set
- Thermal monitoring of transformer automatic shutdown in case of overheating
- Temperature-regulated ventilator reduces noise and dust in the stud welding unit (greater system reliability)
- Control unit galvanically separated from welding lines high degree of functional safety
- Optimal protection against external interferences
- Protection class IP 23
- Also permits operation outdoors

Welding

- **Display** infinitely adjustable power setting; easy monitoring of all functions via LED displays; easy operation via membrane keyboard and digital display; setting of welding parameters, programs, shielding gas, automation and process monitoring possible; digital display of current, welding and gas-preflow time (optional: pneumatic feed time for automation); separate settings for welding current and welding time
- **Powerful** built-in power reserves
- Trouble-free changing of welding voltage polarity possible by reconnecting welding current and ground cables
- Outstanding welding quality very high arc stability even at weak welding currents
- High process flexibility high clock frequency (30 kHz) of stud welding unit allows highly dynamic regulation of welding process

Suitable stud welding guns/ -heads

- A 12, A 16, A 22, A 25, Al 06
- PAH-1
- KAH 412, KAH 412 LA

Issue 11/08

(Technical data may change)